

The Patent Office Concept House Cardiff Road Newport South Wales NP10 8QQ

-GB04/4436

PRIORITY DOCUMENT SUBMITTED OR TRANSMITTED IN SIMPLIANCE WITH RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated

25 October 2004

Patents Form 1/77 - Polician Christian Patents Act 1977 (Rule 16) The Patent Office Request for grant of a patent (See the notes on the back of this form. You can also ge Cardiff Road an explanatory leaflet from the Patent Office to help you fill in Newport this form) · · South Wales NP10 8QQ 1. Your reference MJN/PJE/68218 2. Patent application number 0324700.4 (The Patent Office will fill this part in) 3. Full name, address and postcode of the or of Jon Shipman Contracting Limited each applicant (underline all surnames) 42 Elliott Road Love Lane Industrial Estate Cirencester Gloucestershire GL7 1YS Patents ADP number (if you know it) 6842174002 If the applicant is a corporate body, give the UK (Britain) country/state of its incorporation Title of the invention **TUBING CONNECTION KIT AND METHOD** 5. Name of your agent (if you have one) PAGE HARGRAVE Southgate, Whitefriars "Address for service" in the United Kingdom **Lewins Mead** to which all correspondence should be sent **BRISTOL BS1 2NT** (including the postcode) Patents ADP number (if you know it) 05996483001 6. Priority: Complete this section if you are Country Priority application number Date of filing declaring priority from one or more earlier (if you know it) (day / month / year) patent applications, filed in the last 12 months. 7. Divisionals, etc: Complete this section only if Number of earlier UK application Date of filing this application is a divisional application or (day / month / year) resulted from an entitlement dispute (see note f) 8. Is a Patents Form 7/77 (Statement of inventorship and of right to grant of a patent) Yes required in support of this request? Answer YES if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. Otherwise answer NO (See note d) Patents Form 1/77

Parents Form 1/77

 Accompanying documents: A patent application must include a description of the invention.
 Not counting duplicates, please enter the number of pages of each item accompanying this form:

Continuation sheets of this form

Description 4

Claim(s) 1

Abstract 1

If you are also filing any of the following, state how many against each item.

Priority documents

Drawing(s)

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

atent (Patents Form 7/77)

One

Request for a preliminary examination and search (Patents Form 9/77)

Request for a substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature(s)

PAGÉ HARGRAVE

Date 22/10/03

 Name, daytime telephone number and e-mail address, if any, of person to contact in the United Kingdom

Mr M J Newstead (0117) 927 6634

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered YES in part 8, a Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) Part 7 should only be completed when a divisional application is being made under section 15(4), or when an application is being made under section 8(3), 12(6) or 37(4) following an entitlement dispute. By completing part 7 you are requesting that this application takes the same filing date as an earlier UK application. If you want the new application to have the same priority date(s) as the earlier UK application, you should also complete part 6 with the priority details.

DUPLICATE

-1-

Tubing Connection Kit and Method

This invention concerns the connection of tubing components to pipes, and has particular relevance to air-conditioning systems.

5

The global market for air-conditioning systems has risen dramatically in the last decade and looks set to continue to expand, for example into Eastern Europe. Currently, the most advanced air-conditioning system in common use is the VRV or Variable Refrigerant Volume system. This system comes in two types: "cooling only" which is a two-pipe system, or a three pipe system which performs cooling and heating providing heating through recognised heat-pump technology.

10

15

20

A network of pipes is installed around the building to supply refrigerant to the relevant cooling coils ("air handlers") in the required areas. Figure 1 shows a known apparatus for assembly into such a network. A metal tubing component 1 is shown as a bifurcated Y-shaped junction to be connected to a metal pipe 2. The tube component 1 comprises several sections of different diameter, for example the first branch of the junction has two in-line sections X1 and X2, while the second branch has three in-line sections: Y1, Y2 and Y3 to enable the component to be fitted. to various standard, i.e. commercially accepted, sizes of pipe 2. When the component is to be fitted, the diameter of pipe 2 is determined and the correct diameter section of the component 1" is used to enable the pipe 2 to be accommodated within the section. In the figure shown, section X_2 has the correct diameter to allow pipe 2 to be inserted within it. If however pipe 2 was wider, then section X_1 would have to be used. In that case, the component would be cut off at section X_1 to allow insertion of the pipe 2. To fix the pipe 2 within the end section of component 1, the pipe and section are welded together. This is a cumbersome operation, especially since it is necessary to purge the weld region with nitrogen in order to prevent oxidation of the metal. Accordingly, the connection of tubing component 1 to pipe 2 is intricate and subsequently expensive and prone to error and fire risk, and takes an excessively long time to complete.

25

It is an object of the present invention to provide a connection kit and method which overcome the above problems. This is achieved by the use of cold jointing means with a correspondingly resized tubing component.

30

In accordance with a first aspect of the present invention there is provided a kit of parts comprising a tubing component having at least two in-line sections with different external diameters and a set of connection means, each connection means having dimensions such that it may be joined to the tubing component at a respective section.

5

Preferably, each connection means comprises a locking ring.

The kit of parts may be used in fabricating an air-conditioning system.

10

15

20

In accordance with a second aspect of the present invention there is provided a method of connecting a tubing component to a pipe comprising the steps of:

providing a tubing component with at least two in-line sections with different external diameters;

selecting a section with a substantially similar diameter to that of the pipe;

if the selected section is not at an end of the tubing component, cutting the tubing component in the vicinity of the selected section so that the selected section is at an end of the tubing component;

providing a set of connection means in a range of sizes;

selecting a connection means of suitable dimensions for joining to the selected

section; and

joining the selected connection means to the tubing component at the selected

section.

Preferably, each connection means comprises a locking ring.

25

The invention will now be described by way of example with reference to the following figures, in which:-

Figure 1 shows a conventional pipe assembly;

Figure 2 shows unconnected apparatus according to an embodiment of the present invention; and Figure 3 shows the apparatus of the embodiment in a connected state.

Referring now to Figures 2 and 3, an assembly is shown according to an embodiment of the invention. Starting with Figure 2, again it is desired to connect a tubing component 1' to a pipe 2. The tubing component 1' again comprises several sections of various external diameters, for example the in-line sections X_1' , X_2' , X_3' and X_4' of a first branch and in-line sections Y_1' , Y_2' and Y_3' of a second branch. However, with this embodiment the diameters of the sections are set to be standard, i.e. commercially accepted and available, sizes. Since the pipe 2 is also of a standard diameter, it is possible to select a section which has the same diameter as the pipe 2. In the example shown in the figure, section X_2' has the same diameter as the pipe, and therefore the component is cut at section X_2' as shown. Clearly it is also possible to select a section of the second branch to enable this branch to be connected also.

5

10

15

20 .

25

30

Connection between the component 1' and pipe 2 is achieved by use of a connection means 3, which in the present embodiment comprises a locking ring. A suitable locking ring for this purpose is for example manufactured by Vulkan Lokring, Rohrverbindungen GmbH & Co. KG. of Herne, Germany. Connection is achieved by inserting the ends of the pipe and component into the locking ring as shown, the ends being covered with a sealing preparation beforehand if necessary. A compression device is then used to squeeze the two end rings 4 of the locking ring together, which compresses the ends and holds them tightly and sealingly within the connection, are ratchet arrangement to assist the user in forcing the rings together. A powered compression device is also available, and both of these devices are manufactured by Vulkan Lokring for example. The connected assembly is shown in Figure 3.

The advantage of using such a connection means is that the join can be done cold, i.e. without welding, thus reducing the complexity, time and cost of the assembly operation. Furthermore, no expensive or complex equipment is needed to fit the connection means.

A plurality of connection means of different sizes will be provided, allowing the tubing component to be fitted to a variety of sizes of pipe by appropriate selection of component width section and connection means.

Although the invention has been described with reference to the embodiments above, there are many other modifications and alternatives possible within the scope of the claims. For example, any suitable cold connection means may be used in place of the locking ring.

•

CLAIMS

5

15

20

- 1. A kit of parts comprising a tubing component having at least two in-line sections with different external diameters and a set of connection means, each connection means having dimensions such that it may be joined to the tubing component at a respective section.
- 2. A kit according to Claim 1, wherein each connection means comprises a locking ring.
- 3. A kit of parts according to any preceding claim, for use in fabricating an air-conditioning system.
 - 4. A method of connecting a tubing component to a pipe comprising the steps of:

 providing a tubing component with at least two in-line sections with different external diameters;

 selecting a section with a substantially similar diameter to that of the pipe;

 if the selected section is not at an end of the tubing component, cutting the tubing component in the vicinity of the selected section so that the selected section is at an end of the tubing component;

 providing a set of connection means in a range of sizes;

 selecting a connection means of suitable dimensions for joining to the selected section; and joining the selected connection means to the tubing component at the selected
- 25 5. A method according to Claim 4, wherein each connection means comprises a locking ring.
 - 6. A kit of parts as hereinbefore described with reference to the figures.

section.

7. A method of connecting a tubing component to a pipe as hereinbefore described with reference to the figures.


Abstract

A kit of parts comprises a tubing component 1'having at least two in-line sections with different external diameters and a set of connection means 3, each connection means having dimensions such that it may be joined to the tubing component at a respective section X.


Figure 2

10

5



Prior Art 1.



PCT/**GB**20**04**/00**4436**